



STEAK LOCKER

General Information:	
Item	Steaklocker Professional Edition US / EU
Useable Volume	up to: 520 (L) 18.36 CF
Installation Type	Free Standing / Built In
Temperature Zones	One
Capacity	350 lbs
Number of Shelves	7 Sliding Chrome Food Grade
Temperature Range	33°F - 72°F
Ambient Temperature	28°F - 100.4°F
Warranty	1 year on Parts & Labor including the compressor plus 5 years optional.
Ratings	UL, GS, ETL, CB, ROHS, CE, NSF, ISO9001
Dimensions:	
Steaklocker SLPRO520 US/EU	73.43" H X 23.43" W X 26.77"D
Gross Shipping Weight	Approx: 290 LBS - 128 KG .
Net Weight	Approx: 265 LBS.
Inside Envelope Dimensions	TBA -
Features:	
Shelves	7 Chrome Shelving (food grade)
Temperature Control	Digital Control Panel - Control Buttons
Hygrometer - Controller	Internal Actuator, Digital Hygrometer controller powered by SL PRO Smart App
Germicidal Light	Irridium Bacterial Growth and UV Prevention Light

Glass Door	UV Tinted, Dual Pane, Low E- De-mist
Reversible Door Swing	Choose preferred hinge location
Lock	Yes
Electrical:	
Rated Voltage	110V-120V US Standard / 220V-240V EU Standard
Frequency	60HZ US Standard - 50HZ EU Standard
Rated Power Input	150 Watts
Rated Current	2.0 Amps
Light Power	Max 0.5 Watts
Refrigerant	R600A (90 g)
Energy Consumption	1150 kwh/year
Electrical Requirements	Plugs Directly into US 110 Volt outlet on a Dedicated 15 AMP line.
Decible Rating	41 dB(A)